

# MIDLAND METROLOGY LTD

## Digital Plunger Indicators



110-25

This is a standard model of digital plunger indicator that is reliable and easy to use.

### Key Features

- Large LCD display with clear digital readout and auto power-off function for extended battery life
- Dual scale capability: easily switch between metric (mm) and imperial (inch) units
- Zero reset function available at any measuring position for increased flexibility
- Data output enabled for measurement logging and system integration
- Shock-resistant and dust-proof design ensures durability in workshop environments
- Fitted with a robust, long-lasting contact ball for consistent performance
- Detachable lug back fitting (*feature availability may vary by model*)
- Compact, portable design for ease of use and convenient storage; supplied in a protective case
- Battery included—ready for immediate use straight out of the box

Product	Specification
Digital Indicator 10mm/.4in × .001mm/.00005in	Stem Dia.: 8mm Range & Graduation: 10mm/.4in × .001mm/.00005in
Digital Indicator 10mm/.4in × .01mm/.0005in	Stem Dia.: 8mm Range & Graduation: 10mm/.4in × .01mm/.0005in
Digital Indicator 25mm/1in × .01mm/.0005in	Stem Dia.: 8mm Range & Graduation: 25mm/1in × .01mm/.0005in
Digital Indicator 30mm/1.2in × .01mm/.0005in	Stem Dia.: 8mm Range & Graduation: 30mm/1.2in × .01mm/.0005in
Digital Indicator 50mm/2in × .01mm/.0005in	Stem Dia.: 8mm Range & Graduation: 50mm/2in × .01mm/.0005in

